

(19.8) A cubic unreflected graphite moderated natural uranium reactor contains 3% enriched uranium as UC homogeneously dispersed in the graphite matrix; the weight ratio C/U = 10. The resonance passage and thermal utilization factors are both assumed to be 0.9; $\epsilon = 1.00$. Make an estimate of the critical size of the cube.

$$N_A := 6.022137 \cdot 10^{23} \cdot \text{mole}^{-1} \quad Mw_U := \frac{3 \cdot 235 + 97 \cdot 238}{100} \cdot \text{gm} \cdot \text{mole}^{-1} \quad Mw_C := 12.00 \cdot \text{gm} \cdot \text{mole}^{-1}$$

$$m_U := 1 \cdot \text{kg} \quad \text{assumed for simplicity in calculation of mixture properties}$$

$$m_C := 10 \cdot m_U \quad N_U := \frac{m_U}{Mw_U} \cdot N_A \quad \text{barn} := 10^{-28} \cdot \text{m}^2$$

$$N_{235} := 0.03 \cdot N_U \quad \sigma_{j235} := 98.6 \cdot \text{barn} \quad \sigma_{f235} := 582.2 \cdot \text{barn} \quad v_{235} := 2.418$$

$$N_{238} := 0.97 \cdot N_U \quad \sigma_{j238} := 2.70 \cdot \text{barn} \quad \sigma_{f238} := 0.5 \cdot 10^{-3} \cdot \text{barn}$$

$$\epsilon := 1 \quad p := 0.9 \quad f := 0.9$$

$$x_{235} := \frac{N_{235}}{N_{235} + N_{238}} \quad x_{238} := 1 - x_{235} \quad \alpha := \frac{\sigma_{j235} \cdot x_{235} + \sigma_{j238} \cdot x_{238}}{\sigma_{f235} \cdot x_{235}}$$

$$\eta := \frac{v_{235}}{1 + \alpha} \quad k_{inf} := \eta \cdot \epsilon \cdot p \cdot f \quad k_{inf} = 1.485 \quad L_{m2} := 0.287 \cdot \text{m}^2$$

$$\tau := 0.0380 \cdot \text{m}^2 \quad L_2 := L_{m2} \cdot (1 - f)$$

$$M_2 := L_2 + \tau \quad B_2 := \frac{k_{inf} - 1}{M_2} \quad \text{sidelength} := \sqrt{\frac{33}{B_2}} \quad \text{sidelength} = 2.131 \cdot \text{m}$$